

	COMPANY	SPIRADRILL	HIGHWAY	TEXOMA	WATSON	WATSON
	MODEL	LHD	FD-50	650	1100	2100
Dimensions:	Operational Height (m)	12.04m	12.60m	9.15m	12.40m	15.49m
	Operational Height (ft.)	39'-6"	41'-4"	33'-0"	40'-8"	50'-10"
	Operating weight (lb)	45,000 lbs.	45,000 lbs.		44,840 lbs.	59,480 lbs.
Short mast Units	25' operational height unit available	YES	NO	YES	YES	NO
Power Unit:	Rated Output (HP)	174 hp	125 hp	156 hp	140 hp	173 hp
	Engine Type	John Deere 4045	John Deere 4045	John Deere 6068	John Deere 4045	John Deere 4045
Rotary Drive:	Torque (ft. lbs.)	30,000 ft./lbs.	30,000 ft./lbs.	27,000 ft./lbs.	20,300 ft./lbs.	28,000 ft./lbs.
Crowd System:	Crowd Force (lbs.)	35,000 lbs.	23,550 lbs.	24,500 lbs.	21,300 lbs.	24,000 lbs.
Winches:	Main Winch Line Pull	12,000 lbs.	18,000 lbs.	18,000 lbs.	18,000 lbs.	18,000 lbs.
	Auxiliary Winch	8,000 lbs.	10,000 lbs.	10,000 lbs.	4,500 lbs.	8,500 lbs.
Undercarriage	track or truck	track/truck	truck	track/truck	track/truck	track/truck
Drilling Data:	Drilling depth (ft)	70 ft.	50 ft.	50 ft.	50 ft.	60 ft.
	Drilling Depth (m)	21.33m	15.24m	15.24m	15.24m	18.29m
	Drilling Diameter (m)	1.83m	1.37m	1.52m	1.22m	1.37m
	Drilling Diameter (ft.)	72 inches	54 inches	60 inches	48 inches	54 inches

Note: Data may vary. The information presented is based on available manufacturer's printed information.

We accordingly make no representation with respect to the accuracy or validity of the information, but merely provide it for comparison purposes.